
Sociale 12x24 Glazed Porcelain









03SCL021224FST



03SCL031224FST



1x6 Stacked Mosaic



2x2 Mosaic



03SCL061224FST





03SCL041224FST



03SCL051224FST



QuickSHIP (noted color only)

Tile: 12x24 Feathersoft®

Mosaic: 2x2 Feathersoft®

Special Order

Tile: 12x24 - 24x48 Feathersoft® or Exterior

Mosaic: 1x6 Stacked - 2x4 Stacked

Trim: 4x24 Bullnose - 6x12 Cove Base

Not all colors available in all sizes or finishes

For more information and images:









Test Item	Test Method	Test Result	
Breaking Strength	ASTM C648	> 450 lbf	
Bond Strength	ASTM C482	> 200 psi	
Facial Dimension	ASTM C1026	± 0.10%	
Range of Thickness	ASTM C499	0.035 in	
Warpage Diagonal	ASTM C485	± 0.20%	
Wedging	ASTM C502	± 0.30%	
Frost Resistance	ASTM C1026	Resistant	
Chemical Resistance	ASTM C650	Unaffected	
Water Absorption	ASTM C373	< 0.50%	
Scratch Hardness	Mohs Scale	7	
		Unpolished	Exterior
DCOF	AcuTest	0.50-0.60	0.60-0.70

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.69" x 23.50"	9.5	FeatherSoft® or Exterior	Yes
24" x 48"	23.50" x 47.13"	10.5	FeatherSoft®	Yes
1" x 6" Mosaic	11.69" x 11.42"	9.5	FeatherSoft®	-
2" x 2" Mosaic	11.81" x 11.81"	9.5	FeatherSoft®	-
2" x 4" Mosaic	11.69" x 11.69"	9.5	FeatherSoft®	-
4" x 24" Bullnose	3.82" x 23.50"	9.5	FeatherSoft®	-
6" x 12" Cove Base	5.91" x 11.69"	9.5	Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.





