
## Statuario 12x24 Porcelain









2x2 Mosaic



Tile: 12x24 Mosaic: 2x2

Trim: 4x24 Bullnose

For more information and images:

## Statuario

## Porcelain







## **Technical Characteristics**

| Test Item           | Test Method | Test Result |  |
|---------------------|-------------|-------------|--|
| Breaking Strength   | ASTM C648   | > 400 lbf   |  |
| Bond Strength       | ASTM C482   | > 200 psi   |  |
| Facial Dimension    | ASTM C499   | ± 0.15%     |  |
| Range of Thickness  | ASTM C499   | 0.025"      |  |
| Warpage             | ASTM C485   | ± 0.20%     |  |
| Wedging             | ASTM C502   | ± 0.30%     |  |
| Chemical Resistance | ASTM C650   | Unaffected  |  |
| Frost Resistance    | ASTM C1026  | Resistant   |  |
| Water Absorption    | ASTM C373   | < 0.50%     |  |
| Scratch Hardness    | Mohs Scale  | 7           |  |
| DCOF                | AcuTest     | 0.42-0.52   |  |

| Nominal Size      | Actual Size                 | Thickness | Finish     | Rectified |
|-------------------|-----------------------------|-----------|------------|-----------|
| 12" x 24"         | 11-13/16" x 23-13/16"       | 8.5mm     | Unpolished | -         |
| 2" x 2" Mosaic    | 11-15/16" x 11-15/16" sheet | 8.5mm     | Unpolished | -         |
| 4" x 24" Bullnose | 3-13/16" x 23-13/16"        | 8.5mm     | Unpolished | -         |

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

