

TECH DATA

									
Finish	Freeze Resistant	Shade Variation	Color Body	Water Absorption	Stain Resistant	DCOF AcuTest	Chemical Resistant	Breaking Strength	Mohs Hardness
MATTE SOLID	Resistant	V3	N/A	≤0.5%	Class A	≥.60*	Class A	≥ 275 lbf	8
POL	Resistant	V3	N/A	≤0.5%	Class E	<0.42	Class E	≥ 275 lbf	6
MATTE MIX	N/A	V3	N/A	≤3%	Class A	≥0.42	Class A	≥ 275 lbf	8

* Unless otherwise noted.

PACKING INFO


PRODUCT SIZE INCHES	ACTUAL SIZE	THICKNESS MM	LBS/ CARTON	PCS/ CARTON	SF/ CARTON	SF/ PALLET	LBS/ PALLET	CARTON/ PALLET	NUMBER OF FACES
1x6 Mosaic	11.77x11.77	8.00	36.00	10	10.00	360.00	1,296.00	36	N/A
2x2 Mosaic	11.73x11.73	8.00	36.00	10	10.00	360.00	1,296.00	36	N/A
6x6 Mosaic	5.91x5.91	8.00	18.45	20	20.00	960.00	886.08	48	N/A
12x16	11.65x16.48	8.00	58.40	16	16.00	1,008.00	3,679.20	63	10
12x24	11.70 x 23.50	8.00	52.09	7	13.37	748.72	2,917.04	56	40
24x48	23.50 x 47.13	10.00	76.02	2	15.38	307.60	1,520.40	20	25

For reference only.

AREAS OF USAGE

Classification	Reference Category	Suitable
Interior, Dry	ID	√ POL
Interior, Wet	IW	√ NAT
Interior, Wet Plus	IW+	√ 1x6 2x2 NAT 6x6 MATTE
Exterior, Wet	EW	
Oils/Greases	O/G	

FORMATS



24x48



12x24

GROUT JOINT

The recommended grout joint:

1/8" RECT



60x12 COVE BASE



3x12 BULLNOSE



12x16



12x12



12x12



6x6