

Onice Supreme

12x24 Glazed Porcelain

mosaic 
Products. Design. Solutions.



88ONIMAR1224



Tile: 12x24 - 24x48

Mosaic: N/A

Trim: N/A

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ASTM C373	$\leq 0.5\%$
Breaking Strength	ASTM C648	≥ 350
Scratch Hardness	MOH'S	5
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
PEI - Glazed Tiles	ASTM C1027	IV
Minimum Bond Strength (PSI)	ASTM C482	165
Dynamic Coefficient of Friction (DCOF)	ASTM C1028	≥ 0.42
Facial Dimensions	ASTM C499	Pass
Range of Thickness	ASTM C499	Pass
Warpage	ASTM C485	Pass
Wedging	ASTM C502	Pass

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	9 mm	Lux Matte	Yes
24" x 48"	23.62" x 47.24"	6 mm	Lux Matte	Yes

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.